PRODUCT DATA SHEET

MagLube®

HD-100

Liquid Lubricant

Description

HD-100 is a proprietary blend of organic fatty acid oils and synthetic esters that feature excellent lubricity and thermal stability. HD-100 is blended with a complete package of extreme pressure additives that provides excellent anti-wear characteristics and high burn-off temperature. HD-100 is not water-soluble and is used at full strength.

Applications

HD-100 has excellent lubrication properties that make it useful in a wide variety of applications such as metal forming, wood and rubber processing as well as environmental sensitive applications such as forestry and mining. HD-100 is very cost effective in eliminating the use of flood coolants and the cost of disposal. Minute amounts are delivered directly to the cutting edge of a tool providing excellent heat transfer to the chips and eliminating degradation of the tool. Increased speeds and feeds are common with the proper use of all MagLube products.

Availability

HD-100 is sold in 1 gallon containers, 5 gallon pails, 55 gallon drums and 330 gallon totes.

Safety Compliance

A Material Safety Data Sheet is available for this product on MagLube's website at: www.maglube.com

Contact Us

Mission Allied Group LLC
1535 Oak Industrial Ln, Suite I
Cumming, GA 30041
P: 800-441-2023
F: 770-844-9899
W: www.maglube.com

Copyright © 2011 Mission Allied Group LLC. All Rights Reserved

"Go Lean – Think Green"